

(19)



JAPANESE PATENT OFFICE

PATENT ABSTRACTS OF JAPAN

(11) Publication number: **2001183540 A**

(43) Date of publication of application: **06.07.01**

(51) Int. Cl. **G02B 6/122**  
**G02B 6/12**  
**G02F 1/377**  
**G11B 7/125**  
**G11B 7/135**  
**H01S 5/022**  
**H01S 5/026**

(21) Application number: **2000312717**  
(22) Date of filing: **12.10.00**  
(30) Priority: **15.10.99 JP 11294623**

(71) Applicant: **MATSUSHITA ELECTRIC IND CO LTD**

(72) Inventor: **KITAOKA YASUO**  
**KASASUMI KENICHI**  
**MIZUUCHI KIMINORI**  
**YAMAMOTO KAZUHISA**

(54) **OPTICAL WAVEGUIDE DEVICE, COHERENT LIGHT SOURCE, INTEGRATED UNIT, AND OPTICAL PICKUP DEVICE**

by the slanting surface (4) and projected from the 1st surface (S1) or 2nd surface (S2) of the substrate (1).

(57) Abstract:

COPYRIGHT: (C)2001,JPO

PROBLEM TO BE SOLVED: To solve problems that a coherent light source which uses a conventional optical waveguide device (1) increases in size along the optical axis, (2) induces a light source noise owing to the feedback of a light reflected by a waveguide projection end surface to the light source, and (3) generates an interference noise owing to the rereflection of external reflected light on the optical waveguide projection end surface.

SOLUTION: This optical waveguide device is equipped with a substrate (1) which has a 1st surface (S1) and a 2nd surface (S2) and an optical waveguide (3) which is formed on the 1st surface (S1) of the substrate (1) and has a light incidence end surface and a slanting surface slanting to the optical waveguide (3); and a waveguide light which is made incident on the optical waveguide (3) from the light incidence end surface is totally reflected

